PAGE 1 OF 9

ISSUE DATE: 4/1/2015

I PRODUCT AND COMPANY IDENTIFICATION

GHS PRODUCT IDENTIFIER:

TRADE NAME;

OVEN & GRILL MAINTANENCE CLEANER

OTHER MEANS OF IDENTIFICATION:

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:

RECOMMENDED USE:

FOR FREQUENT CLEANING OF OVENS, GRILLS, FRYERS, HOODS.

SUPPLIER'S DETAILS:

TANNER GROCERY COMPANY 421 MAPLE STREET

CARROLLTON, GA 30117

770-832-6381

24 HR. EMERGENCY NUMBER: INFOTRAC (800)535-5053

II HAZARD IDENTIFICATION

GHS CLASSIFICATION:

GHS CLASSIFICATION SCALE: (1=SEVERE HAZARD, 4=SLIGHT HAZARD)

PHYSICAL HAZARDS:

HEALTH HAZARDS

SKIN CORROSION IRRITATION EYE DAMAGE IRRITATION

CATEGORY 2 CATEGORY 2A

ENVIRONMENTAL HAZARDS:

LABEL ELEMENTS:

SIGNAL WORD: WARNING

HAZARD STATEMENTS:

Causes skin irritation Causes serious eye irritation

PAGE 2 OF 9

HAZARD SYMBOLS:



PRECAUTIONARY STATEMENTS:

Wash hands, face and all exposed skin areas thoroughly after handling. Wear protective gloves/eye protection/face protection

PRECAUTIONARY STATEMENTS (RESPONSE):

IF ON SKIN: Wash with plenty of water. Take off all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IN CASE OF FIRE: Product is not flammable. Fight fire with methods according to surrounding fire.

PRECAUTIONARY STATEMENTS (STORAGE):

No specific GHS directive

PRECAUTIONARY STATEMENTS (DISPOSAL):

No specific GHS directive

OTHER HAZARDS:

Repeated or prolonged exposure can cause skin dryness or cracking.

III PHYSICAL / CHEMICAL CHARACTERISTICS

INGREDIENT IDENTITY	CAS NUMBER	PERCENTAGE	
Sodium Hydroxide	1310-73-2	<1%	
Tetrapotassium pyrophosphate	7320-34-5	1-3	

REMAINING INGREDIENTS ARE NOT REPORTABLE UNDER OSHA/SDS GUIDELINES. THE EXACT PERCENTAGES OF SOME INGREDIENTS HAVE BEEN WITHELD AS (CBI) CONFIDENTIAL BUSINESS INFORMATION TRADE SECRET.

IV FIRST AID MEASURES

INGESTION: If swallowed, call a poison control center immediately. Wash out mouth with water. Do not induce vomiting. If spontaneous vomiting occurs, keep head below hips to prevent aspiration of liquid into the lung. Never give anything by mouth to an unconscious person.

PAGE 3 OF 9

SKIN CONTACT: Remove contaminated clothing. Wash with plenty of water for several minutes. Wash contaminated clothing before reuse. Call a physician if irritation occurs.

INHALATION: Move individual away from exposure and into fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician if symptoms develop or persist or if you feel unwell.

EYE CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses if easy to do. Continue rinsing. Get medical attention/advice.

Most Important Symptoms and Effects, Acute and Delayed

INGESTION: Symptoms may include diarrhea, gastric pain, and vomiting.

SKIN CONTACT: Symptoms may include burning pain, corrosive skin damage, redness, dryness and cracking of skin.

INHALATION: Symptoms may include irritation of respiratory tract

EYE CONTACT: Symptoms may include stinging, tearing, redness, swelling and blurred vision.

Indication of immediate medical attention and special treatment needed, if necessary.

Provide supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call physician immediately, advise of burns of sodium hydroxide.

V FIRE FIGHTING MEASURES

Suitable extinguishing media: Use methods suitable for surrounding fire Unsuitable extinguishing media- Not flammable.

Specific hazards arising from the chemical: hazardous gases could be developed

Hazardous thermal decomposition products: carbon monoxide and CO2

Special protective actions for fire-fighters: Keep product containers and surrounding areas cool with water spray. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters: Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

VI ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material.

PAGE 4 OF 9

Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of information in section 8 for further information. See also information in non-emergency personnel above.

Environmental precautions: Avoid dispersal of spilled material with waterways, drains and sewers. See section 12 for additional ecological information.

Methods and materials for containment and cleaning up.

Small spill: Stop leak if without risk. Move containers from the spill area. Absorb with an inert dry material such as diatomaceous earth or vermiculite and place in an appropriate waste disposal container. Mop any remaining residues with soap and water and dispose of wastes via a licensed waste disposal contractor according to federal, state and local regulations.

Large spill: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, drains, water courses and confined areas. Wash spillages into an effluent treatment plant or absorb with an inert dry material such as diatomaceous earth or vermiculite and place in a appropriate waste disposal containers. Mop any remaining residues with soap and water and dispose of wastes via a licensed waste disposal contractor according to federal, state and local regulations.

VII HANDLING AND STORAGE

Precautions for Safe Handling:

Safe Handling Advice: Utilize appropriate personal protective equipment when handling product. Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mists. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container and tightly closed when not in use. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection and face protection during use. Avoid release to the environment.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional hygiene information.

Conditions for safe storage including any incompatibilities:

Store in original container in a dry, cool and well ventilated area away from strong oxidizing agents (see section 10) and food and drink. Keep container tightly closed when not in use. Do not store in unlabeled containers. Keep away from children.

PAGE 5 OF 9

VIII EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

Ingredient Identity ACGIH TLV OSHA PEL NIOSH IDLH

Sodium Hydroxide

ceiling 2mg/m3

2mg/m3

2mg/m3

1310-73-2

Appropriate Engineering Controls

Engineering Controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants and maintain air concentrations below occupational exposure standards.

Individual protection measures, such as personal protective equipment. (PPE)

Eye/Face Protection: Wear approved tightly sealed safety goggles

Skin & Body Protection: Wear chemical resistant, impervious gloves at all times when handling chemical products. Check during use that gloves are still retaining their impervious properties, as the time for breakthrough can change from different manufacturers and chemical mixtures cannot always be accurately measured. Appropriate footwear and suitable protective clothing should be worn for the degree and risk of exposure.

Respiratory Protection: If workplace exposure limits of product or any component is exceeded, utilize proper respiratory protection program guidelines (see OSHA 1910.134 and American National Standard ANSI Z88.2) Use a properly fitted, NIOSH/MSHA air-purifying or air-fed respirator in compliance with the above mentioned standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

IX PHYSICAL AND CHEMICAL PROPERTIES

Appearance: amber liquid

Odor: detergent

Odor threshold: not available

pH: 10-11

Melting Point/Freezing Point: Not Determined Initial Boiling Point/Range: Not Determined

Flash Pt: Not Applicable

Evaporation Rate: Not Determined (butyl acetate=1)

Lower explosive limits: Not Applicable Upper explosive limits: Not Applicable

Vapor Pressure: Not Determined

Vapor Density: Not Determined (air=1)

Relative Density: 1.21

Solubility in water: Soluble

Partition coefficient: not applicable Auto ignition temp: not applicable Decomposition Temp: not available

Viscosity: water thin

PAGE 6 OF 9

X STABILITY AND REACTIVITY

Reactivity: Reacts with strong acids.

Chemical Stability: Stable under recommended storage conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Avoid contact with strong acids and oxidizers.

Incompatible Materials: Strong acids and oxidizing materials

Hazardous Decomposition Products: Oxides of sodium and irritating fumes and gases.

XI TOXICOLOGICAL INFORMATION

Acute toxicity: Not classified,

Skin corrosion irritation: classified, Category 2, Sodium Hydroxide 1310-73-2 500mg/24hr rabbit skin Causes skin irritation

Serious Eye damage: classified, Category 2A, Sodium Hydroxide, 1310-73-2
400ug eyes-rabbit mild, 1% eyes-rabbit severe
Causes serious eye irritation

Sensitization: Not classified

Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not Classified

Teratogenicity: Not Available

Specific target Organ Toxicity (single exposure):

Not classified or Not available

Specific target Organ Toxicity (repeated exposure)

Not Classified or Not available

TRADE NAME: OVEN & GRILL MAINTANENCE CLEANER

SAFETY DATA SHEET

PAGE 7 OF 9

Aspiration Hazard: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pheumonia.

Information on the likely routes of exposure:

Ingestion: May be harmful if swallowed

Inhalation: May cause respiratory irritation. Prolonged inhalation may be harmful.

Skin: Causes skin irritation

Eye: Causes serious eye irritation

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: See section iv, most important symptoms and effects, acute and delayed. **Inhalation:** See section iv, most important symptoms and effects, acute and delayed.

Skin: See section iv, most important symptoms and effects, acute and delayed. **Eye:** See section iv, most important symptoms and effects, acute and delayed.

Delayed and immediate effects and also chronic effects from short and long term exposure.

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis

Numerical measures of Toxicity

Not Available

XII ECOLOGICAL INFORMATION

FICE:		**	000
To	ХIC		v:

Ingredient name	Result	Species	Exposure
Sodium hydroxide 1310-73-2	69.18mg/l	daphnia	48 hrs
·	250mg/l	fish	96hrs

Persistence and degradability:

Sodium hydroxide- expected to degrade rapidly in air.

Bioaccumulation Potential:

This material is not expected to bioaccumulate

Mobility in Soil:

Not available

Other adverse Effects:

No further information.

XIII DISPOSAL CONSIDERATIONS

Dispose in accordance with applicable federal, state and local regulations.

PAGE 8 OF 9

TRANSPORT INFORMATION

DOT:

UN#:

NOT REGULATED

SHIPPING NAME: NOT REGULATED

HAZARD CLASS: NOT REGULATED

PACKING GROUP: NOT REGULATED

IATA:

NOT DETERMINED

IMDG:

NOT DETERMINED

XV

REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: All ingredients are listed or exempted with TSCA.

SARA 302/304: no ingredients found

Cercla- Sodium hydroxide 1310-73-2

listed

SARA 311/312: acute health hazard: yes; reactive-yes

Ingredient	%	FIRE HAZARD	PRESSURE RELEASE	REACTIVE	IMMEDIATE ACUTE	DELAYED CHRONIC
Sodium	PROPRIETARY			YES	YES	
Hydroxide						
1310-73-2						

SARA 313: no ingredients found

STATE REGULATIONS:

Ingredient	Rhode Island	New Jersey	Massachusetts	Pennsylvania
Sodium Hydroxide		yes	yes	yes
1310-73-2				

California Prop 65: none known to meet requirements.

TRADE NAME: OVEN & GRILL MAINTANENCE CLEANER

SAFETY DATA SHEET

PAGE 9 OF 9

XVI OTHER INFORMATION

HMIS RATING: HEALTH (3) FIRE (0) REACTIVITY (1)

4=EXTREME, 3=HIGH, 2=MODERATE, 1=SLIGHT, 0=INSIGNIFICANT

NOTICE TO READER:

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. The information on this sds was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Users are advised to confirm in advance of need, that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the sds. /furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.